INDUSTRIAL COMPONENT DATA

# G-ESIS-M20-S68N-NEPDS-S 1415125 PHOENIX CONTACT Cable gland

**Brand: PHOENIX CONTACT | Manufacturer Part Number: G-ESIS-M20-S68N-NEPDS-S**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | G-ESIS-M20-S68N-NEPDS-S |
| Catalog number | 1415125 |
| Category | Cable gland |
| Minimum order | 10 Pcs |
| Document ID | EO-CCE6D4DE50 |
| Generated | 2026-11-19 |

## Product Overview

Cable gland
Cable gland, screwed connection material: Brass, nickel-plated, application: Ex, outer diameter of the cable 6 mm ... 13 mm, shielding: no, connection thread: M20 x 1.5, color: silver, with O-ring

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial plug-in connectors/interfaces |

## Additional Product Information

Key Commercial Data
Orderkey 1415125
Packing unit 10 pc
Catalog page Page 555 (C-3-2017)
GTIN 4055626037868
Weight per Piece (excluding packing) 22.220 g
Custom tariff number 74199990
Country of origin DE (Germany)
Dimensions
Length 43 mm
Thread pitch 1.5 mm
Wrench size, union nut 24 mm
Wrench size, support 24 mm

Hexagon angular dimension 27 mm
Length of the connecting thread 12 mm
External cable diameter 6 mm ... 13 mm
Cable types that can be used for unarmored cables
Hole diameter 20.1 mm ... 20.3 mm
Ambient conditions
Degree of protection (IP) IP66
IP68 (5 bar / 0.5 h)
Ambient temperature (operation) -40 °C ... 75 °C (static)
General
Cable gland material Nickel-plated brass
Material grommet GRP EPDM (O-ring)
Cable seal material EPDM
Material, insert PA
Thread type connection side M20 x 1.5
Torque 8 Nm (Support sleeve)
Tightening torque, union nut 8.00 Nm
Color silver
Manufacturer WISKA
Manufacturer Designation EMSKE-L 20
Suited for EX-applications yes
Standards and Regulations
ATEX II 2 G/D EEx e II IP68
IECEx Ex e IIC Gb, Ex tb IIIC Db
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 5.127149100eCl@ss 6.027149100eCl@ss 7.027149109eCl@ss 8.027149109eCl@ss 9.027144432
ETIM 5.0EC000441ETIM 6.0EC000441
UNSPSC 13.239121311

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-ESIS-M20-S68N-NEPDS-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.