INDUSTRIAL COMPONENT DATA

G-INS-M32-M68N-PNES-BK 1411136 PHOENIX CONTACT Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INS-M32-M68N-PNES-BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INS-M32-M68N-PNES-BK
Catalog number	1411136
Category	Cable gland
Minimum order	5 Pcs
Document ID	EO-C0FD3073F1
Generated	2026-11-19

Product Overview

Cable gland
Cable gland, screwed connection material: PA, outer diameter of the cable 15 mm ... 21 mm, shielding: no, connection thread: M32 x 1.5, colour: deep black RAL 9005

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1411136
Packing unit 5 pc
Minimum order quantity 5 pc
Catalog page Page 694 (C-2-2017)
GTIN 4046356922685
Weight per Piece (excluding packing) 27.070 g
Custom tariff number 39269097
Country of origin TR (Turkey)
Dimensions
Length 50 mm
Wrench size, union nut 36 mm
Wrench size, support 36 mm

Hexagon angular dimension 40.9 mm
Length of the connecting thread 10 mm
Feed-through hole diameter 32.1 mm ... 32.3 mm
External cable diameter 15 mm ... 21 mm
16 mm ... 21 mm (for UL 514 B)
Ambient conditions
Degree of protection (IP) IP68 (5 bar / 0.5 h)
IP66
Ambient temperature (operation) -20 °C ... 100 °C (static)
General
No. of conductors 1
Cable gland material PA
Cable seal material Neoprene
Flammability rating according to UL 94 V2
V2 (Housing)
Shielded no
Thread type connection side M32 x 1.5
Thread type on connection side M32
Torque 5 Nm (Union nut: EN 62444)
5 Nm (Support: EN 62444)
8 Nm (for UL514 B: union nut)
Color jet black RAL 9005
Impact category 4
Execution of the strain relief A
Assembly instructions 1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque
Manufacturer BIMED
Manufacturer Designation BM-EN-24
Standards and Regulations
Halogen-free no
Connection in acc. with standard CSA
Flammability rating according to UL 94 V2
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INS-M32-M68N-PNES-BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.