INDUSTRIAL COMPONENT DATA

G-INS-N1/2-S68L-PNES-GY 1411153 PHOENIX CONTACT Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INS-N1/2-S68L-PNES-GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-INS-N1/2-S68L-PNES-GY
Catalog number	1411153
Category	Cable gland
Minimum order	10 Pcs
Document ID	EO-9E89A854FA
Generated	2026-11-19

Product Overview

Cable gland
Cable gland, screw connection material: PA, outer diameter of the cable 10 mm ... 14 mm, shielding: no, connection thread: 1/2 in. NPT, color: silver gray RAL 7001

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data
Orderkey 1411153
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 683 (C-4-2015)
GTIN 4046356922883
Weight per Piece (excluding packing) 14.980 g
Custom tariff number 39269097
Country of origin TR (Turkey)
Dimensions
Length 47 mm
Wrench size, union nut 27 mm
Wrench size, support 27 mm

Hexagon angular dimension 30.8 mm
Length of the connecting thread 15 mm
External cable diameter 10 mm ... 14 mm
10 mm ... 14 mm (for UL 514 B)
Ambient conditions
Degree of protection (IP) IP68 (5 bar / 0.5 h)
IP66
Ambient temperature (operation) -20 °C ... 100 °C (static)
General
No. of conductors 1
Cable gland material PA
Cable seal material Neoprene
Flammability rating according to UL 94 V2
V2 (Housing)
Shielded no
Thread type connection side 1/2 inch NPT
Thread type on connection side 1/2 inch NPT
Torque 2 Nm (Union nut: EN 62444)
2 Nm (Support: EN 62444)
9 Nm (for UL514 B: union nut)
Color silver-gray RAL 7001
Assembly instructions 1) Mount screw connection support in the housing using the correct torque 2) Insert cable 3) Tighten union nut using the correct torque
Manufacturer BIMED
Manufacturer Designation BSPC-02
Standards and Regulations
Halogen-free no
Connection in acc. with standard CSA
Flammability rating according to UL 94 V2
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.127149100eCl@ss 6.027149100eCl@ss 7.027149109eCl@ss...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INS-N1/2-S68L-PNES-GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.