INDUSTRIAL COMPONENT DATA

# G-INB-M32-M68N-PEPDS-BK 1415181 PHOENIX CONTACT Cable gland

**Brand: PHOENIX CONTACT | Manufacturer Part Number: G-INB-M32-M68N-PEPDS-BK**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | G-INB-M32-M68N-PEPDS-BK |
| Catalog number | 1415181 |
| Category | Cable gland |
| Minimum order | 5 Pcs |
| Document ID | EO-1FC3CCD4F5 |
| Generated | 2026-11-19 |

## Product Overview

Cable gland
Cable gland, screwed connection material: PA, outer diameter of the cable 13 mm ... 21 mm, shielding: no, connection thread: M32 x 1.5, colour: deep black RAL 9005, with torsion protection

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial plug-in connectors/interfaces |

## Additional Product Information

Key Commercial Data
Orderkey 1415181
Packing unit 5 pc
Minimum order quantity 5 pc
Catalog page Page 704 (C-2-2017)
GTIN 4055626038124
Weight per Piece (excluding packing) 62.560 g
Custom tariff number 39269097
Country of origin DE (Germany)
Dimensions
Length 138 mm
Wrench size, union nut 36 mm
Wrench size, support 36 mm

Hexagon angular dimension 40 mm
Length of the connecting thread 12 mm
Feed-through hole diameter 32.1 mm ... 32.3 mm
External cable diameter 13 mm ... 21 mm
17.4 mm ... 26.4 mm (for UL 514 B)
Ambient conditions
Degree of protection (IP) IP68 (5 bar / 0.5 h)
IP69 (DIN EN 60529 / IEC 60529)
Ambient temperature (operation) -40 °C ... 100 °C (static)
General
Type with bend protection sleeve
No. of conductors 1
Cable gland material PA
Sealing material EPDM (Cable seal, halogen-free)
Glow wire ignition temperature GWIT according to EN 60695-2-13 750.00
Shielded no
Thread type connection side M32 x 1.5
Thread type on connection side M32
Torque 4 Nm (Union nut: EN 62444)
15 Nm (Support: EN 62444)
Color jet black
Impact category 4
Execution of the strain relief A
Manufacturer WISKA
Manufacturer Designation ESKVS 32
Standards and Regulations
Halogen-free yes
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 5.127149100eCl@ss 6.027149100eCl@ss 7.027149109eCl@ss 8.027149109eCl@ss 9.027144432
ETIM 5.0EC000441ETIM 6.0EC000441
UNSPSC 13.239121311

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-INB-M32-M68N-PEPDS-BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.