

INDUSTRIAL COMPONENT DATA

G-ESS-M40-L66L-STES-S 1411082 PHOENIX CONTACT Cable gland

Brand: PHOENIX CONTACT | Manufacturer Part Number: G-ESS-M40-L66L-STES-S



Manufacturer	PHOENIX CONTACT
MPN / Reference	G-ESS-M40-L66L-STES-S
Catalog number	1411082
Category	Cable gland
Minimum order	2 Pcs
Document ID	EO-F42A8E5607
Generated	2026-09-23

Product Overview

Cable gland

Cable gland, screwed connection material: 316L stainless steel, application: Ex, cable outer diameter 23.5 mm ... 32.2 mm, shielding: no, connection thread: M40 x 1.5, color: silver

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Key Commercial Data

Orderkey 1411082

Packing unit 2 pc

Minimum order quantity 2 pc

Note Made to Order (non-returnable)

Catalog page Page 556 (C-3-2017)

GTIN 4046356921961

Weight per Piece (excluding packing) 184.850 g

Custom tariff number 73182900

Country of origin GB (United Kingdom)

Dimensions

Length 43 mm

Thread pitch 1.5 mm

Wrench size, union nut 50 mm

Wrench size, support 50 mm

Hexagon angular dimension 55 mm

Length of the connecting thread 15 mm

External cable diameter 23.5 mm ... 32.2 mm

Cable types that can be used for unarmored cables

Ambient conditions

Degree of protection (IP) IP66 (using the corresponding A-SEW-...P-W flat gasket)

IP67 (using the corresponding A-SEW-...P-W flat gasket)

IP68 (using the corresponding A-SEW-...P-W flat gasket)

Ambient temperature (operation) -60 °C ... 130 °C (static)

General

Material Stainless steel 316L

Cable gland material Stainless steel 316L

Cable seal material EPDM

Thread type connection side M40 x 1.5

Color silver

Impact energy 20.00 J

Assembly instructions Sealed to IP66/IP67/IP68 thanks to the use of the A-SEW-40-P-W flat gasket (item 1411286)

Standards/specifications EN 60079-0, -1, -7, -15, -31

IEC 60079-0, -1, -7, -15, -31

EN 50262

BS 6121: Part 1:1989

IEC 62444

Manufacturer CMP

Manufacturer Designation A2F1RA, thread size 40

Suited for EX-applications yes

Standards and Regulations

Standards/regulations EN 60079-0, -1, -7, -15, -31

IEC 60079-0, -1, -7, -15, -31

EN 50262

BS 6121: Part 1:1989

ATEX Sira 13ATEX1068X

Sira 13A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / G-ESS-M40-L66L-STES-S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.