INDUSTRIAL COMPONENT DATA

# LS-WMTB-AL (40X15) 0831501 PHOENIX CONTACT Cable marker

**Brand: PHOENIX CONTACT | Manufacturer Part Number: LS-WMTB-AL (40X15)**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | LS-WMTB-AL (40X15) |
| Catalog number | 0831501 |
| Category | Cable coding system |
| Minimum order | 5 Pcs |
| Document ID | EO-A0CBB5399D |
| Generated | 2026-11-19 |

## Product Overview

Cable marker
Cable marker, Aluminum plate, aluminum color, unlabeled, labelable with: TOPMARKNEO, TOPMARK LASER, mounting class: Mounting with cable tie, cable diameter: > 4.6 mm, useful surface: 40x15mm, Number of individual indexes: 16
Cable label, Tag made of aluminium, aluminium, blank, can be labelled with: TOPMARK NEO, TOPMARK LASER, mounting type: Cable tie mounting, cable diameter: > 4.6 mm, Number of individual tags: 16, height of the text field: 15 mm, width of the text field: 40 mm

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > MS Material |

## Additional Product Information

Key Commercial Data
Orderkey 0831501
Packing unit 5 pc
Minimum order quantity 5 pc
Catalog page Page 197 (C-3-2017)
GTIN 4046356924757
Weight per Piece (excluding packing) 68.200 g
Custom tariff number 76169990
Country of origin CN (China)
Dimensions

Length (b) 58 mm
Width (a) 15 mm
Material thickness (g) 0.80 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 120 °C (At temperatures above 80 °C there might be a slight change to the material surface)
General
Color aluminum color
Type Card form
Components free from silicone, halogen, and cadmium
Material Aluminum
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 16
Printability Direct laser marking
Device 0831831 TOPMARK LASER
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Procedure
Test duration 96 h
Note The information does not apply to the color fastness of the material.
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Procedure A
Test duration 96 h
Note The information does not apply to the color fastness of the material.
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type Assembly with cable binders
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classificat...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LS-WMTB-AL (40X15) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.