INDUSTRIAL COMPONENT DATA

WMTB-AL (D30) 0830804 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMTB-AL (D30)



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMTB-AL (D30)
Catalog number	0830804
Category	Cable coding system
Minimum order	90 Pcs
Document ID	EO-622376953C
Generated	2026-11-19

Product Overview

Cable marker
Cable marker, Aluminum plate, aluminum color, unlabeled, labelable with: BLUEMARKIDCOLOR, BLUEMARKID, BLUEMARK CLED, mounting class: Mounting with cable tie, cable diameter: > 2.4 mm, useful surface: d 30 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0830804
Packing unit 90 pc
Minimum order quantity 90 pc
Note Made to Order (non-returnable)
Catalog page Page 201 (C-3-2017)
GTIN 4046356780780
Weight per Piece (excluding packing) 1.490 g
Custom tariff number 76169990
Country of origin DE (Germany)
Dimensions
Length (b) 30 mm
Width (a) 30 mm
Material thickness (g) 0.80 mm

Ambient conditions
Recommended storage conditions 5°C to 25°C
General
Color aluminum color
Type Roll
Components free from silicone, halogen, and cadmium
Material Aluminum
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Printability UV LED technology
Device 5147999 BLUEMARK CLED
5146662 BLUEMARK CLED-FLUID-CARTR.
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification following DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type Assembly with cable binders
Min. cross section 4 mm²
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027149103eCl@s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMTB-AL (D30) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.