INDUSTRIAL COMPONENT DATA

LS-WMTB-AL (100X15) BK 0831511 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: LS-WMTB-AL (100X15) BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	LS-WMTB-AL (100X15) BK
Catalog number	0831511
Category	Cable coding system
Minimum order	5 Pcs
Document ID	EO-9063DB7B0F
Generated	2026-11-19

Product Overview

Cable marker
Cable marker, Aluminum plate, black, unlabeled, labelable with: TOPMARKNEO, TOPMARK LASER, mounting class: Mounting with cable tie, cable diameter: > 4.6 mm, useful surface: 100x15mm, Number of individual indexes: 8
Cable marker, aluminium sign, black, unlabelled, can be written on: TOPMARK NEO, TOPMARK LASER, mounting type: cable tie mounting, cable diameter: > 4.6 mm, number of individual labels: 8, text field height: 15 mm, text field width: 100 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0831511
Packing unit 5 pc
Minimum order quantity 5 pc
Catalog page Page 197 (C-3-2017)
GTIN 4046356925136
Weight per Piece (excluding packing) 68.870 g
Custom tariff number 76169990
Country of origin DE (Germany)
Dimensions

Length (b) 118 mm
Width (a) 15 mm
Material thickness (g) 0.80 mm
Ambient conditions
Ambient temperature (operation) -25 °C ... 70 °C
General
Color black
Type Card form
Components free from silicone, halogen, and cadmium
Material Aluminum
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 8
Printability Direct laser marking
Device 0831831 TOPMARK LASER
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Procedure
Test duration 96 h
Note The information does not apply to the color fastness of the material.
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Procedure A
Test duration 96 h
Note The information does not apply to the color fastness of the material.
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type Assembly with cable binders
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 5.127400400eCl@ss 6.027400400eCl@ss 7.027400401eCl@ss 8.027400401eCl@ss 9.0274004...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LS-WMTB-AL (100X15) BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.