INDUSTRIAL COMPONENT DATA

# US-WMTB (29X8) OG CUS 0830013 PHOENIX CONTACT Cable marker

**Brand: PHOENIX CONTACT | Manufacturer Part Number: US-WMTB (29X8) OG CUS**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | US-WMTB (29X8) OG CUS |
| Catalog number | 0830013 |
| Category | Cable coding system |
| Minimum order | 1 Pcs |
| Document ID | EO-1565C5065E |
| Generated | 2026-11-18 |

## Product Overview

Cable marker
Cable marker, available: per card, orange, labelled according to customer specifications, mounting type: Mounting with cable tie, cable diameter: > 13 mm, usable area: 29x8mm, Number of individual indexes: 24
Cable marker, Card, can be ordered: by card, orange, labeled according to customer specifications, mounting type: Assembly with cable ties, cable diameter: > 13 mm, Number of individual labels: 24, text field height: 8 mm, text field width: 29 mm

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > CABINET add-on |

## Additional Product Information

Technical dataProduct propertiesProduct type Labeled conductor marker
Type Card form
Data management status
Article revision 01
Marking
Number of individual labels 24
Number of individual labels per row 6
Identification technology Thermal transfer for sheets and cards
MountingMounting type Assembly with cable ties
Material specificationsColor orange (RAL 2003)

Material PVC
Flammability rating according to UL 94 V0
Components Silicone-free
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Ambient conditions
Ambient temperature (operation) -30 °C ... 80 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport) 23 °C
Recommended humidity (storage/transport) 50 %
Shelf life 12 months
DimensionsWidth 16 mm
Text field width 29.00 mm
Text field height 8.00 mm
Length 29 mm
External dimensions
Outside diameter > 13 mm ... 136 mm
Standards and regulationsWipe resistance DIN EN 61010-1 (VDE 0411-1)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / US-WMTB (29X8) OG CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.



Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.