INDUSTRIAL COMPONENT DATA

LS-WMTB-AL (100X15) CUS 0831789 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: LS-WMTB-AL (100X15) CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	LS-WMTB-AL (100X15) CUS
Catalog number	0831789
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-F8BBF18E25
Generated	2026-11-19

Product Overview

Cable marker
Cable marker, Aluminum plate, available: per piece, aluminum color, labeled according to customer specifications, mounting class: Mounting with cable tie, cable diameter: > 4.6 mm, useful surface: 100 x 15 mm, Number of individual indexes: 8

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0831789
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 247 (NTK-2014)
GTIN 4046356929912
Weight per Piece (excluding packing) 99.990 g
Custom tariff number 76169990
Country of origin DE (Germany)
Dimensions
Length (b) 118 mm
Width (a) 15 mm
Material thickness (g) 0.80 mm

Ambient conditions
Ambient temperature (operation) -25 °C ... 120 °C (At temperatures above 80 °C there might be a slight change to the material surface)
General
Color aluminum color
Type Card form
Components free from silicone, halogen, and cadmium
Material Aluminum
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Printability Direct laser marking
Device 0831831 TOPMARK LASER
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Procedure
Test duration 96 h
Note The information does not apply to the color fastness of the material.
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Procedure A
Test duration 96 h
Note The information does not apply to the color fastness of the material.
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type Assembly with cable binders
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 5.127400...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LS-WMTB-AL (100X15) CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.