INDUSTRIAL COMPONENT DATA

WML 3 (13X10)A4 CUS 0830699 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML 3 (13X10)A4 CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML 3 (13X10)A4 CUS
Catalog number	0830699
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-ABDDD1FBFE
Generated	2026-11-18

Product Overview

Cable marker
Cable marker, available: Elbow, white, labeled according to customer's instructions, mounting class: glued, cable diameter: <= 3 mm, usable surface: 13 x 10 mm, Number of individual indices: 156

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0830699
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 193 (C-5-2013)
GTIN 4046356718837
Weight per Piece (excluding packing) 99.990 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 19 mm
Width (a) 13 mm
Ambient conditions

Ambient temperature (operation) -40 °C ... 150 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color white
Base element material Vinyl film
Type Label
Components Free from halogen and cadmium
Material Polyester
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 156
Number of individual labels per row 12
Adhesive Acrylic
Printability Office printing systems
Plotter
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 4.024190218eCl@ss 4.124190218eCl@ss 5.027141137eCl@ss 5.127400400eCl@ss 6.027400400eCl@ss 7.027400401eCl@ss 8.027400401eCl@ss 9.027400401
ETIM 3.0EC000761ETIM 4.0EC001530ETIM 5.0EC001530ETIM 6.0EC001530
UNSP...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML 3 (13X10)A4 CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.