INDUSTRIAL COMPONENT DATA

WML 5 (25X10)A4 YE 0830690 PHOENIX CONTACT Cable marker label

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML 5 (25X10)A4 YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML 5 (25X10)A4 YE
Catalog number	0830690
Category	Cable coding system
Minimum order	10 Pcs
Document ID	EO-2DEAE57082
Generated	2026-11-19

Product Overview

Cable marker label
Cable marker label, Elbow, yellow, unlabeled, labelable with: Office printing systems, CMS-P1-PLOTTER, PLOTMARK, mounting class: glued, cable diameter range: 3.2 ... 5.1 mm, cable diameter: <= 5.1 mm, usable area: 25x10mm, Number of individual indexes: 70

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0830690
Packing unit 10 pc
Minimum order quantity 10 pc
Note Made to Order (non-returnable)
Catalog page Page 224 (C-3-2017)
GTIN 4046356718752
Weight per Piece (excluding packing) 15.410 g
Custom tariff number 39269092
Country of origin DE (Germany)
Dimensions
Length (b) 25.4 mm

Width (a) 25 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 150 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Note Print image may vary depending on laser printer
Color yellow
Base element material Vinyl film
Type Label
Components Free from halogen and cadmium
Material Polyester
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 70
Number of individual labels per row 7
Adhesive Acrylic
Printability Office printing systems
Plotter
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027149103eCl@ss 5.127400400eCl@ss 6.027400400eCl@ss 7.027400401eCl@ss 8.027400401eCl@...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML 5 (25X10)A4 YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.