INDUSTRIAL COMPONENT DATA

WML-RFID/HF 14 (25X19)R 0803386 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML-RFID/HF 14 (25X19)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML-RFID/HF 14 (25X19)R
Catalog number	0803386
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-0C641888E9
Generated	2026-11-18

Product Overview

Cable marker
Cable marker label with RFID-HF transponder, roll, white, unlabeled, labelable with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X1.2, mounting type: adhesive, cable diameter: min. 9 mm, cable diameter: max. 14 mm, usable area: 25 x 19 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0803386
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 225 (C-3-2017)
GTIN 4055626047751
Weight per Piece (excluding packing) 499.000 g
Custom tariff number 85235200
Country of origin DE (Germany)
Dimensions
Length (b) 63 mm
Width (a) 25 mm

Cable diameter 6 mm ... 14 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 85 °C
Recommended storage conditions 20°C/50% relative humidity. Storage in the original packaging is recommended.
General
Color white
Base element material PVC
Type Label
Components Free from silicone and cadmium
Material PVC
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 750
Number of individual labels per row 1
Adhesive Acrylic
Device 5146477 THERMOMARK ROLL
5146723 THERMOMARK ROLL X1
5146231 THERMOMARK X1.2
Ink ribbon 5145384 THERMOMARK-RIBBON 110
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type adhesive
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 5.1 27400400 eCl@ss 6.0 27400400 eCl@ss 7.0 2740040...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML-RFID/HF 14 (25X19)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.