INDUSTRIAL COMPONENT DATA

WML 3 (13X10)R CUS 0824884 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML 3 (13X10)R CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML 3 (13X10)R CUS
Catalog number	0824884
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-A371119FA2
Generated	2026-11-18

Product Overview

Cable marker
Cable marker, available: by lines, white, labeled according to customer's instructions, mounting class: glued, cable diameter: <= 3 mm, usable surface: 13 x 10 mm
Cable marker, available: by lines, white, labelled according to customer specifications, mounting class: glued, cable diameter range: 3 ... 3 mm, cable diameter: <= 3 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data
Orderkey 0824884
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 195 (C-5-2013)
GTIN 4046356358071
Weight per Piece (excluding packing) 1.990 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 19 mm

Width (a) 12.7 mm
Ambient conditions
Ambient temperature (operation) -50 °C ... 110 °C
Recommended storage conditions 23 °C / 50% relative humidity. Storage in poly bags is recommended prior to processing.
General
Color white
Base element material Vinyl film
Type Label
Components Silicone-free
Material PVC
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels per row 4
Adhesive Acrylic
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146723 THERMOMARK ROLL X1
5146257 THERMOMARK S1.1
5146231 THERMOMARK X1.2
Ink ribbon 5145384 THERMOMARK-RIBBON 110
0829544 THERMOMARK-RIBBON 110 BU
0829542 THERMOMARK-RIBBON 110 GN
0829543 THERMOMARK-RIBBON 110 RD
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML 3 (13X10)R CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.