INDUSTRIAL COMPONENT DATA

WMT 5,5 (15X8)R 0817248 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMT 5,5 (15X8)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMT 5,5 (15X8)R
Catalog number	0817248
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-F1D87D443C
Generated	2026-11-18

Product Overview

Cable marker
Cable marker, Roll, white, unlabeled, labelable with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting class: slip, cable diameter range: 4 ... 5.5 mm, usable area: 15 x 8 mm, Number of individual indexes: 4000
Cable marker, Roll, white, unlabeled, labelable with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting class: slip, cable diameter range: 4 ... 5.5 mm, Number of individual indexes: 4000, Text field height: 8 mm, Text field width: 15 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0817248
Packing unit 1 pc
Catalog page Page 238 (C-3-2017)
GTIN 4046356125710
Weight per Piece (excluding packing) 752.400 g
Custom tariff number 39269097
Country of origin DE (Germany)
Dimensions

Length (b) 34.4 mm
Width (a) 8 mm
Cable diameter 4 mm ... 5.5 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
Recommended storage conditions 23 °C / 50 % relative humidity
General
Color white
Type Roll
Components free from silicone and halogen
Material Polyester
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 4000
Number of individual labels per row 2
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146723 THERMOMARK ROLL X1
5146231 THERMOMARK X1.2
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Foil strength 175 µm
Marking mounting type thread on
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 4.024190...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMT 5,5 (15X8)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.