INDUSTRIAL COMPONENT DATA

WMT 8,4 (17X10)R 0817251 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMT 8,4 (17X10)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMT 8,4 (17X10)R
Catalog number	0817251
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-A8AD4846AF
Generated	2026-11-18

Product Overview

Cable marker
Cable marker, Roll, white, unlabeled, labelable with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting class: slip, cable diameter range: 5 ... 8.4 mm, usable area: 17 mm x 10 mm, Number of individual indexes: 4000
Cable marker, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: slide-on, cable diameter range: 5 ... 8.4 mm, Number of individual labels: 4000, text field height: 10 mm, text field width: 17 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking
Type Roll
Data management status
Article revision 02
Marking
Number of individual labels 4000
Number of individual labels per row 2
Identification technology Thermal transfer for rolls
DimensionsWidth 10 mm

Text field width 17.00 mm
Text field height 10.00 mm
Length 44.4 mm
External dimensions
Outside diameter 5 mm ... 8.4 mm
Material specificationsFoil strength 175 µm
Color white (RAL 9010)
Material Polyester
Components free from silicone and halogen
Cable/lineExternal cable diameter 5 mm ... 8.4 mm
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-1):2011-07
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl
[CAS No. 67-63-0] Test passed
n-Hexane
[CAS No. 110-54-3] Test passed
Water + Petroleum ether
[CAS No. 64742-82-1] Test passed
Testing in a condensation changing climate in the presence of sulfur dioxide
Specification DIN 50018:2013-05
Result Test passed
Climate level AHT 1.0 S
Cycles 2
Salt spray test
Specification DIN EN 60068-2-11:2000-02
Result Test passed
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
Recommended storage conditions 23 °C / 50 % relative humidity
Recommended ambient temperature (storage/transport) 23 °C
Recommended humid...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMT 8,4 (17X10)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.