INDUSTRIAL COMPONENT DATA

WMTB HF (40X12)R RD 0803314 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: WMTB HF (40X12)R RD



Manufacturer	PHOENIX CONTACT
MPN / Reference	WMTB HF (40X12)R RD
Catalog number	0803314
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-AF89A1221E
Generated	2026-11-18

Product Overview

Cable marker
Cable marker, Roll, red, unlabeled, labelable with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting class: Cable mounting, cable diameter: >= 6 mm, usable area: 40 x 12 mm, Number of individual indexes: 1000

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0803314
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 240 (C-3-2017)
GTIN 4055626024332
Weight per Piece (excluding packing) 1,060.600 g
Custom tariff number 39204910
Country of origin DK (Denmark)
Dimensions
Length (b) 40 mm
Width (a) 10 mm

Ambient conditions
Ambient temperature (operation) -25 °C ... 80 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color red
Type Roll
Components halogen-free
Flammability rating according to UL 94 V0
Material PUR
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 1000
Number of individual labels per row 1
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146723 THERMOMARK ROLL X1
5146231 THERMOMARK X1.2
Ink ribbon 5148007 THERMOMARK-RIBBON 110-WMTB HF
0802990 TM-RIBBON 110-WMTB HF WH
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Note The information does not apply to the color fastness of the material.
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions IEC 61010-1:2010-06
Result Test passed
Marking mounting type Assembly with cable binders...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WMTB HF (40X12)R RD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.