INDUSTRIAL COMPONENT DATA

LS-WMTB-V4A (D30) 0831521 PHOENIX CONTACT Cable marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: LS-WMTB-V4A (D30)



Manufacturer	PHOENIX CONTACT
MPN / Reference	LS-WMTB-V4A (D30)
Catalog number	0831521
Category	Cable coding system
Minimum order	5 Pcs
Document ID	EO-963842CBD2
Generated	2026-11-18

Product Overview

Cable marker
Cable marker, Stainless steel plate, silver, unlabeled, labelable with: TOPMARKNEO, TOPMARK LASER, mounting class: Mounting with cable tie, cable diameter: > 2.9 mm, useful surface: 26x13mm, Number of individual indexes: 20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0831521
Packing unit 5 pc
Minimum order quantity 5 pc
Catalog page Page 199 (C-3-2017)
GTIN 4046356925310
Weight per Piece (excluding packing) 100.840 g
Custom tariff number 73269098
Country of origin CN (China)
Dimensions
Length (b) 30 mm
Width (a) 30 mm
Material thickness (g) 0.50 mm

Ambient conditions
Ambient temperature (operation) -80 °C ... 400 °C
General
Color silver
Type Card form
Components free from silicone, halogen, and cadmium
Material V4A
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 20
Printability Direct laser marking
Device 0831831 TOPMARK LASER
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Alternating condensation climate with SO2 test specification following DIN 50018:2013-05
Climate level AHT 1.0 S
Cycles 2
Condensation test result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type Assembly with cable binders
Standards and Regulations
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Classifications
eCl@ss 5.127400400eCl@ss 6.027400400eCl@ss 7.027400401eCl@ss 8.027400401eCl@ss 9.027400401
ETIM 4.0EC0015...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / LS-WMTB-V4A (D30) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.