INDUSTRIAL COMPONENT DATA

WML-FLAG 6 (20X10)R 0830711 PHOENIX CONTACT Cable marking flags

Brand: PHOENIX CONTACT | Manufacturer Part Number: WML-FLAG 6 (20X10)R



Manufacturer	PHOENIX CONTACT
MPN / Reference	WML-FLAG 6 (20X10)R
Catalog number	0830711
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-7CBCE65280
Generated	2026-11-18

Product Overview

Cable marking flags
Cable wrapping label, Roll, white, unlabeled, labelable with: THERMOMARKE.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting class: glued, cable diameter: <= 6 mm, useful surface: 20x10mm, Number of individual indexes: 2500

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Key Commercial Data
Orderkey 0830711
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 227 (C-3-2017)
GTIN 4046356724555
Weight per Piece (excluding packing) 524.900 g
Custom tariff number 39199080
Country of origin DE (Germany)
Dimensions
Length (b) 20 mm
Width (a) 10 mm

Ambient conditions
Ambient temperature (operation) -40 °C ... 60 °C
Ambient temperature (assembly) > 5 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color white
Base element material Vinyl film
Type Label
Components free from silicone and halogen
Material Polyolefine
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 2500
Number of individual labels per row 1
Printability Thermal transfer
Device 5146477 THERMOMARK ROLL
5146723 THERMOMARK ROLL X1
0804501 THERMOMARK ROLLMASTER 300
0804663 THERMOMARK ROLLMASTER 600
Ink ribbon 5145384 THERMOMARK-RIBBON 110
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Test duration 96 h
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type adhesive
Standards and Regulations
Wipe resist...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WML-FLAG 6 (20X10)R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.