INDUSTRIAL COMPONENT DATA

SAC-3P- 1,5-PUR/M12FR P 1442670 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-1,5-PUR/M12FR P



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-1,5-PUR/M12FR P
Catalog number	1442670
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-B0710B80BE
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 3-pole, halogen-free PUR, greyish black RAL 7021, free cable end, to Elbow connection female M12, coding: A, cable length: 1.5 m, with plastic knurling
Sensor/actuator cable, 3-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket angled M12, coding: A, cable length: 1.5 m, with plastic knurl

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable
Application Standard
Number of positions 3
No. of cable outlets 1
Shielded no
Coding A
Insulation characteristics
Overvoltage category II
Degree of pollution 3
Material specificationsFlammability rating according to UL 94 HB
Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection PA
Electrical propertiesInsulation resistance >= 100 M?
Nominal voltage UN 250 V AC
250 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles >= 100
SignalingStatus display no
Status display present No
Connection dataConductor connection
Tightening torque 0.4 Nm (M12 connector)
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket angled M12
Number of positions 3
Coding type A
Cable/lineCable length 1.5 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 23 kg/km
UL AWM Style 20549
Number of positions 3
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 3x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.27 mm ±0.02 mm (Signal line)
External cable diameter 3.85 mm ±0.15 mm
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, blue, b...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-1,5-PUR/M12FR P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.