INDUSTRIAL COMPONENT DATA

SAC-3P-M8Y/2X3,0-PUR/M 8FS 1458693 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-M8Y/2X3,0-PUR/M 8FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-M8Y/2X3,0-PUR/M 8FS
Catalog number	1458693
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-444791BA27
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/Actuator Cable, 3-Pole Halogen-Free, M8 Straight Connector, Coding: A, to M8 Straight Female and M8 Straight Female, Cable Length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1458693
Packing unit 1 pc
Catalog page Page 254 (C-2-2017)
GTIN 4046356638043
Weight per Piece (excluding packing) 155.800 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 3 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
Degree of protection IP65

IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 3
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M8 connector IEC 61076-2-104
Status display No
Overvoltage category II
Degree of pollution 3
Torque 0.2 Nm (M8 knurl)
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Standard designation M8 connector
Standards/regulations IEC 61076-2-104
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549
Conductor cross section 3x 0.25 mm²
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm
Thickness, insulation >= 0.21 mm (Core insulation)
Wire colors brown, blue, black
Overall twist 3 wires, twisted
Length of twist, overall twist 40 mm
External sheath, color black...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-M8Y/2X3,0-PUR/M 8FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.