INDUSTRIAL COMPONENT DATA

SAC-3P-MR/ 0,3-PUR/A-1L-Z SCO 1434934 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-MR/ 0,3-PUR/A-1L-Z SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-MR/ 0,3-PUR/A-1L-Z SCO
Catalog number	1434934
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-09293892B0
Generated	2026-11-18

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 3-pole halogen-free, M12 angled connector, coding: A SPEEDCON, a A valve connectors, with 1 LED, connected with Diode Z, cable length: 0.3 m
Sensor/actuator cable, 3-pole, halogen-free PUR, grayish black RAL 7021, M12 SPEEDCON angled connector, coding: A, a Valve connectors A, with 1 LED, Circuit: Diode Z, cable length: 0.3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1434934
Packing unit 1 pc
Catalog page Page 234 (C-2-2017)
GTIN 4046356413329
Weight per Piece (excluding packing) 44.400 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 0.3 m
Central screw valve connector M3 x 29

Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
-20 °C ... 85 °C (valve plug)
Degree of protection IP65
IP67
General
Rated current at 40°C 4 A
Rated voltage 24 V AC
24 V DC
Number of positions 3
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Valve connector EN 175301-803
Status display 1 LED
Protective circuit/component Z diode
Pulse power Wmax 40 W (at 100 µs square-wave pulse)
Terminal voltage 70 V (at 2 mA constant current)
Reverse voltage 50 V
Overvoltage category III
Degree of pollution 3
Insertion/withdrawal cycles >= 100 (M12 connector)
Torque 0.4 Nm (M12 connector)
0.6 Nm (Valve connector)
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Valve plug contact material CuSn
Valve plug contact surface material Sn
Valve plug contact insert material PA 6.6
Material housing valve plug TPU
Material, knurls Zinc die-cast, nickel-plated
Sealing material TPU (Seal molded)
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Standard designation Valve connector
Standards/regulation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-MR/ 0,3-PUR/A-1L-Z SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.