INDUSTRIAL COMPONENT DATA

# SAC-4P-M12MR/0,6-PUR/M12FS 1668603 PHOENIX CONTACT Sensor/actuator cable

**Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MR/0,6-PUR/M12FS**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | SAC-4P-M12MR/0,6-PUR/M12FS |
| Catalog number | 1668603 |
| Category | Sensor-actuator patch cord |
| Minimum order | 1 Pcs |
| Document ID | EO-FA9B807168 |
| Generated | 2026-11-18 |

## Product Overview

Sensor/actuator cable
Sensor/actuator cable, 4-pole, halogen-free PUR, greyish black RAL 7021, Elbowed male connector M12, coding: A, to Straight connection female M12, coding: A, cable length: 0.6 m

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Industrial Field Connectivity (IFC) |

## Additional Product Information

Key Commercial Data
Orderkey 1668603
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 200 (C-2-2017)
GTIN 4017918136055
Weight per Piece (excluding packing) 32.900 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 0.6 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 4
Insulation resistance >= 10 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549 / 10493 (80°C/300 V)
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm
Thickness, insulation >= 0.21 mm
Wire col...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MR/0,6-PUR/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.