INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/ 1,5-PUR/M12FS P 1442858 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 1,5-PUR/M12FS P



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/ 1,5-PUR/M12FS P
Catalog number	1442858
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-E94AF64CF2
Generated	2026-11-18

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 4-pole, halogen-free PUR, greyish black RAL 7021, Straight connector M12, coding: A, to Straight female M12, coding: A, cable length: 1.5 m, with plastic knurling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1442858
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 132 (PC-2011)
GTIN 4046356535762
Weight per Piece (excluding packing) 50.000 g
Custom tariff number 85444290
Country of origin PL (Poland)
Dimensions
Length of cable 1.5 m
Ambient conditions
Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 4
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Polyamide
Sealing material NBR
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549 / 10493 (80°C/300 V)
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm
Thickness, insulation >= 0.21 mm
Wire colors brown, white, bl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 1,5-PUR/M12FS P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.