INDUSTRIAL COMPONENT DATA

SAC-5P- 1,5-430/MINFR PWR 1443352 PHOENIX CONTACT Power cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P- 1,5-430/MINFR PWR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P- 1,5-430/MINFR PWR
Catalog number	1443352
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-6E7FE65561
Generated	2026-11-18

Product Overview

Power cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1443352
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 278 (C-4-2015)
GTIN 4046356536912
Weight per Piece (excluding packing) 311.000 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 1.5 m
Ambient conditions
Ambient temperature (operation) -40 °C ... 90 °C (Socket)
Degree of protection IP65
IP67

IP68
General
Rated current at 40°C 10 A
Rated voltage 63 V DC
Rated surge voltage 4000 V
Number of positions 5
Color handle area black
Insulation resistance >= 10 M?
Coding A - standard
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Structure of individual litz in acc. with VDE 0295 / smallest wire diameter VDE 0295 class 5
Insertion/withdrawal cycles 100
Material
Flammability rating according to UL 94 HB
Contact material CuZn
Contact surface material AU
Contact carrier material PA 6.6
Material of grip body TPU
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Flame resistance UL 1581, Sec. 1061 (Cable Flame)
IEC 60332-1-2
Flammability rating according to UL 94 HB
Cable
Cable type PVC gray
Cable type (abbreviation) 430
UL AWM style 21098 (90 °C / 600 V)
Conductor cross section 5x 1.5 mm²
AWG signal line 16
Conductor structure, voltage supply 30x 0.25 mm
Wire colors Black 1, black 2, black 3, black 4, green/yellow
Overall twist 5 cores, twisted
External sheath, color gray RAL 7001
External cable diameter D 10 mm
Minim...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P- 1,5-430/MINFR PWR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.