INDUSTRIAL COMPONENT DATA

SAC-5P-M12MR/10,0-PUR 1694460 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-5P-M12MR/10,0-PUR



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-5P-M12MR/10,0-PUR
Catalog number	1694460
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-1D24AA88DD
Generated	2026-11-19

Product Overview

Sensor/actuator cable
Sensor/actuator cable, 5-pole, halogen-free PUR, greyish black RAL 7021, M12 angled male connector, coding: A, to free cable end, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1694460
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 207 (C-2-2017)
GTIN 4017918178338
Weight per Piece (excluding packing) 313.000 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 10 m
Stripping length of the free conductor end 50 mm
Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)
Degree of protection IP65
IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 5
Insulation resistance >= 100 M?
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles >= 100
Torque 0.4 Nm (M12 connector)
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
UL AWM style 20549
Conductor cross section 5x 0.34 mm² (Signal line)
AWG signal line 22
Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ±0.02 mm (Signal line)
Thickness, insu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-5P-M12MR/10,0-PUR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.