INDUSTRIAL COMPONENT DATA

VS-PPC/PL-PPC/PL-93K-LI/5,0 1419181 PHOENIX CONTACT Patch cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PPC/PL-PPC/PL-93K-LI/5,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PPC/PL-PPC/PL-93K-LI/5,0
Catalog number	1419181
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-719F966190
Generated	2026-11-18

Product Overview

Patch cable
Sercos III cable, shielded, star quad, flexible AWG 22 (7 wires), RAL 3020 (red), RJ45/IP67 push-pull plug, plastic to RJ45/IP67 push-pull plug, plastic, length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1419181
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 317 (PC-2011)
GTIN 4046356541268
Weight per Piece (excluding packing) 391.000 g
Custom tariff number 85444210
Country of origin PL (Poland)
Ambient conditions
Degree of protection IP65
IP67
Ambient temperature (operation) -40 °C ... 70 °C (cable, fixed installation)

-40 °C ... 70 °C (cable, flexible installation)
General data
Number of positions 4
Overvoltage category I
Degree of pollution 2
Locking type Push Pull
Characteristics head 1
Material (component) Plastic
Characteristics head 2
Material (component) Plastic
Standards and Regulations
Flammability rating according to UL 94 V0
Cable
Cable type Sercos III
Cable type (abbreviation) 93K
UL AWM style 21694 (60°C / 600 V)
Signal type/category Sercos CAT5 (IEC 11801), 100 Mbps
Cable structure 1x4xAWG22/7; SF/TQ
Conductor cross section 4x 0.34 mm²
AWG signal line 22
Conductor structure signal line 7x 0.25 mm
Core diameter including insulation approx. 1.55 mm
Wire colors White, yellow, blue, orange
Type of pair shielding Aluminum-lined polyester foil
Overall twist Star quad
Shielding Tinned copper braided shield
External sheath, color signal red RAL 3020
Outer sheath thickness approx. 0.9 mm
External cable diameter D 6.5 mm ±0.2 mm
Minimum bending radius, fixed installation 3 x D
Minimum bending radius, flexible installation 7 x D
Cable weight 68 kg/km
Outer sheath, material PVC
Material, inner sheath PVC
Material condu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PPC/PL-PPC/PL-93K-LI/5,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.