INDUSTRIAL COMPONENT DATA

K-5E OE/5,0-C02/M23 FK 1620416 PHOENIX CONTACT Cable plug in molded plastic

Brand: PHOENIX CONTACT | Manufacturer Part Number: K-5E-OE/5,0-C02/M23 FK



Manufacturer	PHOENIX CONTACT
MPN / Reference	K-5E-OE/5,0-C02/M23 FK
Catalog number	1620416
Category	Power cable less 1 kV, for moving application
Minimum order	2 Pcs
Document ID	EO-2B99D40652
Generated	2026-11-19

Product Overview

Cable plug in molded plastic
Plastic-coated cable plug, length: 5 m, outer wrap colour: orange RAL 2003
Moulded cable conductors, KSF, M23-Female, angled, swivelling, -120° left / 120° right, number of poles: 5+PE, locking type: Screw locking, cable length: 5 m, shielded: yes, outer sheath colour: orange RAL 2003

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1620416
Packing unit 1 pc
Minimum order quantity 2 pc
Note Made to Order (non-returnable)
Catalog page Page 227 (C-2-2017)
GTIN 4046356831758
Weight per Piece (excluding packing) 1,200.000 g
Custom tariff number 85444290
Country of origin DE (Germany)
Conductor length 5 m
Nominal current 18 A

Connector specifications
Type Angled, can be turned, plastic-coated
Thread type M23
Locking type Screw locking
Degree of protection IP67, when in locked state
Number of positions 5+PE
Direction of rotation Standard
Type of contact Socket
Insertion/withdrawal cycles 50
Contact resistance < 0.3 m?
Max. current 30 A
Voltage 630 V
Overvoltage category III
Degree of pollution 3
Rated surge voltage 6 kV
Ambient temperature (operation) -40 °C ... 105 °C
Cable specifications
Type of cable PSLC11Y-J
Shielded yes
Cable structure 4x 1.5 mm² + 2x 1.5 mm²
Cable structure (AWG) 16 AWG/4c + 16 AWG/1pr
External cable diameter 12.3 mm
Outer sheath, material PUR
Material wire insulation TPM
External sheath, color orange RAL 2003
Nominal voltage, cable 600 V
Test voltage 4 kV
Rated current 18 A
Smallest bending radius, movable installation 123 mm
Ambient temperature for fixed installation -40 °C ... 80 °C
Ambient temperature for flexible installation -20 °C ... 70 °C
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Cl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / K-5E-OE/5,0-C02/M23 FK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.