INDUSTRIAL COMPONENT DATA

SAC-3P-100,0-PVC/0,25 1501854 PHOENIX CONTACT Cable reel

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-3P-100,0-PVC/0,25



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-3P-100,0-PVC/0,25
Catalog number	1501854
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-E9BC3D2B41
Generated	2026-11-18

Product Overview

Cable reel
By meters, Cable ring, PVC, black RAL 9005, 3-conductors, color single conductors: brown, blue, black, cable length: 100 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1501854
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 304 (C-2-2017)
GTIN 4017918813987
Weight per Piece (excluding packing) 2,170.960 g
Custom tariff number 85444995
Country of origin DE (Germany)
Dimensions
Length of cable 100 m
General
Number of positions 3

Cable
Cable type PVC black
Cable type (abbreviation) PVC
Cable abbreviation LiYY
Conductor cross section 3x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.25 mm ±0.02 mm
Thickness, insulation >= 0.23 mm (Core insulation)
Wire colors brown, blue, black
Overall twist 3 wires, twisted
External sheath, color black RAL 9005
Outer sheath thickness >= 0.76 mm
External cable diameter D 4.4 mm ±0.15 mm
Cable weight 29 kg/km
Outer sheath, material PVC
Material conductor insulation PVC
Conductor material Bare Cu litz wires
Insulation resistance >= 100 M?*km (at 20 °C)
Conductor resistance max. 78 ?/km (at 20 °C)
Nominal voltage, cable >= 300 V
Test voltage, cable <= 3000 V
Flame resistance As per UL-Style 2464
Ambient temperature (operation) -25 °C ... 80 °C (cable, fixed installation)
-5 °C ... 80 °C (cable, flexible installation)
Environmental Product Compliance
China RoHS Environmentally friendly use period: unlimited = EFUP-e
No hazardous substances above threshold values
Classifications
eCl@ss 10.0.127060106eCl@ss 4.027060306eCl@ss 4.127060306eCl@ss 5.027061801eCl@ss 5.127061800eCl@ss 6.027062000eCl@s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-3P-100,0-PVC/0,25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.