INDUSTRIAL COMPONENT DATA

SAC-6P-100,0-PUR/0,25 1550614 PHOENIX CONTACT Cable reel

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-6P-100,0-PUR/0,25



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-6P-100,0-PUR/0,25
Catalog number	1550614
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-A86FDF0F8C
Generated	2026-11-18

Product Overview

Cable reel
By meters, Cable ring, halogen-free PUR, grayish black RAL 7021, 6-conductors, color single conductors: brown, white, blue, black, gray, pink, cable length: 100 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1550614
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 304 (C-2-2017)
GTIN 4046356170420
Weight per Piece (excluding packing) 3,307.900 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 100 m
General
Number of positions 6

Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y
Conductor cross section 6x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm
Thickness, insulation >= 0.21 mm (Core insulation)
Wire colors brown, white, blue, black, gray, pink
Overall twist Six cores around the filler to the core
External sheath, color black-gray RAL 7021
Outer sheath thickness approx. 0.7 mm
External cable diameter 5.00 mm
External cable diameter D 5 mm ±0.15 mm
Cable weight 34 kg/km
Outer sheath, material PUR
Material, filler PE
Material conductor insulation PP
Conductor material Bare Cu litz wires
Insulation resistance >= 100 M?*km (at 20 °C)
Conductor resistance 78 ?/km (at 20 °C)
Nominal voltage, cable <= 300 V
Test voltage, cable >= 3000 V
Special properties Flexible cable conduit capable
Silicone-free
Free of substances which would hinder coating with paint or varnish
Flame resistance in accordance with DIN UL-Style 20549
Halogen-free in accordance with DIN VDE 0472 part 815
Resistance to oil in accordance with DIN EN 60811-2-1
Other resistance Highly resistant....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-6P-100,0-PUR/0,25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.