INDUSTRIAL COMPONENT DATA

# FLK 50/4X14/EZ-DR/ 300/KONFEK 2296728 PHOENIX CONTACT Cable

**Brand: PHOENIX CONTACT | Manufacturer Part Number: FLK 50/4X14/EZ-DR/ 300/KONFEK**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | FLK 50/4X14/EZ-DR/ 300/KONFEK |
| Catalog number | 2296728 |
| Category | PLC connection cable |
| Minimum order | 1 Pcs |
| Document ID | EO-09C543B3EE |
| Generated | 2026-11-18 |

## Product Overview

Cable
Ready-made round cable; Connection 1: Female IDC/FLK connection (1x 50-poles); connection 2: IDC/FLK connection female (4x 14-poles); Cable length: 3 m

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > INTERFACE Components (IF) |

## Additional Product Information

Key Commercial Data
Orderkey 2296728
Packing unit 1 pc
Catalog page Page 551 (C-5-2017)
GTIN 4017918593742
Weight per Piece (excluding packing) 676.700 g
Custom tariff number 85444290
Country of origin DE (Germany)
General
Nominal voltage UN < 50 V AC
60 V DC
Max. current carrying capacity per path 1 A
Max. conductor resistance 0.16 ?/m

Length of cable 3 m
Single wire, cross section 0.14 mm²
Single wire, cross section [AWG] 26
Conductor construction: Number of litz wires: 7
Single wire, material Cu tin-plated
External diameter 6.3 mm
Cable, preassembly Insulation displacement, IEC 60352-4/DIN EN 60352-4
Shielding no
Environmental conditions
Ambient temperature (operation) -20 °C ... 50 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
Flame resistance IEC 60332-1
DIN VDE 0482 Part 332-1
Connector 1
Connection name Field level
Connection method IDC/FLK socket strip
Number of connections 4
Number of positions 14
Pitch 2.54 mm
Connector 2
Connection name Controller level
Connection method IDC/FLK socket strip
Number of connections 1
Number of positions 50
Pitch 2.54 mm
Supported controller
Controller SIEMENS S7-400
- suitable I/O card 6ES7 421-1BL01-0AA0
6ES7 422-1BL00-0AA0
6ES7 422-7BL00-0AB0
Controller ALLEN-BRADLEY ControlLogix
- suitable I/O card 1756-IB32
1756-OB32
Controller ALLEN-BRADLEY PLC 5
- suitable I/O card 1771 IBN
1771 OBN
Controller HONEYWELL Experion PKS C200
- suitable I/O card TC-IDD 321
TC-ODD 321
Controller Schneider Electric Modicon TSX QUANTUM
-...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLK 50/4X14/EZ-DR/ 300/KONFEK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.