INDUSTRIAL COMPONENT DATA

CARRIER 35-13 3059117 PHOENIX CONTACT End clamp

Brand: PHOENIX CONTACT | Manufacturer Part Number: CARRIER 35-13



Manufacturer	PHOENIX CONTACT
MPN / Reference	CARRIER 35-13
Catalog number	3059117
Category	End bracket for terminal block
Minimum order	100 Pcs
Document ID	EO-7506BA57F2
Generated	2026-11-18

Product Overview

End clamp
End support, material:PA, color:gray
End bracket, material: PA, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type End bracket
Data management status
Article revision 01
DimensionsWidth 13 mm
Height 53.3 mm
Depth on NS 32 52.1 mm
Depth on NS 35/7,5 47.1 mm
Depth on NS 35/15 54.6 mm
Length 53.3 mm
Material specificationsColor gray (RAL 7042)
Material PA
Flammability rating according to UL 94 V0
Static insulating material application in cold -60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C

Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Environmental and real-life conditionsAmbient conditions
Ambient temperature (operation) -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly) -5 °C ... 70 °C
Ambient temperature (actuation) -5 °C ... 70 °C
Permissible humidity (storage/transport) 30 % ... 70 %
MountingMounting type NS 35/7,5
NS 35/15
NS 32

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CARRIER 35-13 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.