INDUSTRIAL COMPONENT DATA

SD-WMTB (70X10) VA 0826585 PHOENIX CONTACT Carrier for conductor marking collar

Brand: PHOENIX CONTACT | Manufacturer Part Number: SD-WMTB (70X10) VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SD-WMTB (70X10) VA
Catalog number	0826585
Category	Cable coding system
Minimum order	50 Pcs
Document ID	EO-95FBAE0A7F
Generated	2026-11-18

Product Overview

Carrier for conductor marking collar
Conductor identification sleeve holder, silver, unlabeled, mounting class: Mounting with cable ties, cable diameter: > 16 mm, usable surface: 70 x 10 mm
Carrier for conductor marking collar, silver, unlabeled, mounting type: Assembly with cable ties, cable diameter: > 16 mm, text field height: 10 mm, text field width: 70 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataProduct propertiesProduct type Marker carrier cable
Type Marking strip/label
Data management status
Article revision 00
DimensionsWidth 10 mm
Text field width 70.00 mm
Text field height 10.00 mm
Length 70 mm
External dimensions
Outside diameter 10 mm ... 305 mm
Material specificationsColor silver

Material Stainless steel
Cable/lineExternal cable diameter > 16.00 mm
Environmental and real-life conditionsScratch test for the determining scratch resistance
Specification DIN EN ISO 1518-1:2019-10 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2013 (following)
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-1):2011-07
DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl
[CAS No. 67-63-0] Test passed
n-Hexane
[CAS No. 110-54-3] Test passed
Water + Petroleum ether
[CAS No. 64742-82-1] Test passed
Specification ISO 175:2010 (following)
Test duration 168 h
Ambient conditions
Ambient temperature (operation) -80 °C ... 400 °C
Recommended ambient temperature (storage/transport) 23 °C
Recommended humidity (storage/transport) 50 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life 24 months
Standards and regulationsWipe resistance DIN EN 61010-1 (VDE 0411-1)
MountingMounting type Assembly with cable ties

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SD-WMTB (70X10) VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES
Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.