INDUSTRIAL COMPONENT DATA

FLK 50-PA/EZ-DR/HF/KS/ 500/YUC 2904636 PHOENIX CONTACT Front adapters

Brand: PHOENIX CONTACT | Manufacturer Part Number: FLK 50-PA/EZ-DR/HF/KS/ 500/YUC



Manufacturer	PHOENIX CONTACT
MPN / Reference	FLK 50-PA/EZ-DR/HF/KS/ 500/YUC
Catalog number	2904636
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-25877C5A6B
Generated	2026-11-19

Product Overview

Front adapters
Cast iron front adapter with halogen-free fixed round cable and a 50-pole plug pin extruded on both sides for connecting Yokogawa control systems. Cable length: 5.0 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)

Additional Product Information

Key Commercial Data
Orderkey 2904636
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 516 (C-5-2017)
GTIN 4046356868389
Weight per Piece (excluding packing) 1,080.000 g
Custom tariff number 85444290
Country of origin DE (Germany)
Ambient conditions
Ambient temperature (operation) -20 °C ... 70 °C
Ambient temperature (storage/transport) -20 °C ... 70 °C
General

Max. permissible operating voltage 30 V DC
Max. permissible current 500 mA (per path at 70°C)
Connection data 1
Connection name Control side
Connection method Yokogawa, I/O cards compatible
Torque 0.5 Nm (Screw connection)
Number of connections 1
Number of positions 50
Connection data 2
Connection name Field level
Connection method Yokogawa, KS compatible
Torque 0.5 Nm (Screw connection)
Number of connections 1
Number of positions 50
Cable
Conductor construction: Number of litz wires: 7
Single wire, material Cu tin-plated
Single wire, cross section 0.14 mm²
External diameter 11 mm
Shielding Tinned copper-braided shield, approx. 85% covering
Length of cable 5 m
External sheath, color gray RAL 7035
Shielding yes
Halogen-free cable Yes
Cable insulation resistance >= 20 M?/km
Cable resistance <= 145 ?/km
Supported controller
Controller YOKOGAWA CS3000 CentumVP
- suitable I/O card ADV151
ADV551
Controller YOKOGAWA STARDOM
- suitable I/O card NFDV151
NFDV551
Standards and Regulations
Flame resistance IEC 60332-3-22
IEC 60332-1-2
VDE 0842, Part 332-1-2
Resistance to oil against occasional splashes
Gasolin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FLK 50-PA/EZ-DR/HF/KS/ 500/YUC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.