INDUSTRIAL COMPONENT DATA

VS-OE-OE-94D-100,0 1416334 PHOENIX CONTACT Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-OE-OE-94D-100,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-OE-OE-94D-100,0
Catalog number	1416334
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-A59DEE5DED
Generated	2026-11-18

Product Overview

Network cable
Network cable, CAT5 Ethernet (1 GBit/s), 8-pole, shielded, free cable end, to free cable end, cable length: 100 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1416334
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 397 (C-2-2017)
GTIN 4046356474559
Weight per Piece (excluding packing) 4,790.000 g
Custom tariff number 85444290
Country of origin DE (Germany)
Dimensions
Length of cable 100 m
General data
Number of positions 8
Signal type/category Ethernet CAT5, 1 Gbps

Cable
Cable type Ethernet
Cable type (abbreviation) 94D
UL AWM style 2464 (80°C/300 V)
Signal type/category Ethernet CAT5 (IEC 11801), 1 Gbps
Cable structure 4x2xAWG26/7; SF/UTP
Conductor cross section 4x 2x 0.14 mm²
AWG signal line 26
Conductor structure signal line 7x 0.16 mm
Core diameter including insulation 0.98 mm ±0.05 mm
Wire colors white/blue-blue, white/orange-orange, white/green-green, white/brown-brown
Twisted pairs 2 cores to the pair
Overall twist 4 pairs, twisted
Shielding Aluminum-lined polyester foil, tinned copper braided shield
Optical shield covering 85 %
External sheath, color black RAL 9005
Outer sheath thickness 0.8 mm
External cable diameter D 6.4 mm ±0.2 mm
Smallest bending radius, fixed installation 30 mm
Smallest bending radius, movable installation 60 mm
Tensile strength GRP 80 N
Outer sheath, material PVC (reinforced) UV-resistant
Material conductor insulation PP
Conductor material Bare Cu litz wires
Insulation resistance >= 5 G?*km
Conductor resistance < 140 ?/km
Cable capacity < 56 nF/km
Wave impedance 100 ? ±15 ? (at 4 ... 100 MHz)
Signal speed 0.6 c
Nominal voltage, cable 72 V DC
300 V....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-OE-OE-94D-100,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.