INDUSTRIAL COMPONENT DATA

CC 2,5/ 2-GSF-5,08 P26THRR32 1092853 PHOENIX CONTACT Housing base printed circuit board, nominal current: 12..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CC 2,5/ 2-GSF-5,08 P26THRR32

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	CC 2,5/ 2-GSF-5,08 P26THRR32
Catalog number	1092853
Category	Printed circuit board connector
Minimum order	1320 Pcs
Document ID	EO-8ADB420051
Generated	2026-11-19

Product Overview

Housing base printed circuit board, nominal current: 12 A, number of poles: 2, pitch: 5,08 mm, color: black, surface of contact: Tin, assembly: Soldering THR
Printed circuit board base case, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of rows: 1, number of poles: 2, family of articles: DC 2.5/.. -GSF, pitch: 5.08 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, lock: Screw lock, fixing type: Air clamping (thread), packaging type: 32 mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CC 2,5/ 2-GSF-5,08 P26THRR32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.