INDUSTRIAL COMPONENT DATA

TFKC 2,5/ 3-STF-5,08 BD:US2-NC 1704803 PHOENIX CONTACT Plug-in part, rated current: 12 A, number of poles: 3..

Brand: PHOENIX CONTACT | Manufacturer Part Number: TFKC 2,5/ 3-STF-5,08 BD:US2-NC

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	TFKC 2,5/ 3-STF-5,08 BD:US2-NC
Catalog number	1704803
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-8FC1AF8D32
Generated	2026-11-19

Product Overview

Plug-in part, rated current: 12 A, number of poles: 3, pitch: 5.08 mm, connection type: Push-in spring connection, color: green, contact surface: Tin
Connector for printed circuit board, nominal section: 2.5 mm², color: green, nominal current: 12 A, dimensioning voltage (III/2): 320 V, contact surface: Tin, contact type: Female connection, Number of potentials: 3, Number of rows: 1, Number of poles per row: 3, number of connections: 6, family of articles: TFKC 2.5/.. -STF, pitch: 5.08mm, connection type: Push-in spring connection, conductor/printed circuit board connection direction: 0°, Stecksystem: CLASSIC COMBICON, Locking: Screw lock, Packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Plug component, nominal current: 12 A, number of positions: 3, pitch: 5.08 mm, connection method: Push-in spring connection, color: green, contact surface: Tin
Your advantages
Time saving push-in connection, tools not requiredPotentials can be easily looped through - ideal for BUS applicationsIntuitive use through colour coded actuation leverCan be combined with the MSTB 2´,5 rangeScrewable flange for superior mechanical stabilityKey Commercial Data
Orderkey 1704803

Packing unit 1
GTIN 4046356738927
Custom tariff number 85366990
General
Range of articles TFKC 2,5/..-STF
Type of contact Female connector
Number of positions 3
Connection method Push-in spring connection
Rated voltage (III/3) 320 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Nominal cross section 2.5 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 12
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. 0.5 mm²
2 conductor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / TFKC 2,5/ 3-STF-5,08 BD:US2-NC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.