INDUSTRIAL COMPONENT DATA

CCV 2,5/16-GF-5,08-LR P26THR 1827799 PHOENIX CONTACT Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: CCV 2,5/16-GF-5,08-LR P26THR



Manufacturer	PHOENIX CONTACT
MPN / Reference	CCV 2,5/16-GF-5,08-LR P26THR
Catalog number	1827799
Category	Printed circuit board connector
Minimum order	52 Pcs
Document ID	EO-FB027FD1C1
Generated	2026-11-19

Product Overview

Printed-circuit board connector
Printed circuit board base housing, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of potentials: 16, number of rows: 1, number of poles: 16, number of connections: 16, family of articles: CCV 2.5/.. -GF-LR, pitch: 5.08 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of solder pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, lock: Snap-in lock, fixing type: Lock & Release air clamping (thread), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1827799
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
GTIN 4046356953306
Weight per Piece (excluding packing) 6.630 g
Custom tariff number 85366930
Country of origin DE (Germany)
Dimensions

Length [l] 8.57 mm
Width 91.39 mm
Pitch 5.08 mm
Dimension a 76.2 mm
Width [w] 91.39 mm
Height [h] 14.6 mm
Height 12 mm
Length of the solder pin 2.6 mm
Pin dimensions 1 x 1 mm
Length 8.57 mm
General
Range of articles CCV 2,5/..-GF-LR
Insulating material group IIIa
Rated surge voltage (III/3) 4 kV
Rated surge voltage (III/2) 4 kV
Rated surge voltage (II/2) 4 kV
Rated voltage (III/3) 250 V
Rated voltage (III/2) 320 V
Rated voltage (II/2) 400 V
Connection in acc. with standard EN-VDE
Nominal current IN 12 A
Insulating material LCP
Flammability rating according to UL 94 V0
Color black
Number of positions 16
Standards and Regulations
Connection in acc. with standard EN-VDE
Flammability rating according to UL 94 V0
Environmental Product Compliance
REACh SVHC Lead 7439-92-1
China RoHS Environmentally Friendly Use Period = 50
For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”
Classifications
eCl@ss 5.127260700eCl@ss 6.027260700eCl@ss 7.027440402eCl@ss 8.027440402eCl@ss 9.027440402
ETIM 4.0EC002637ETIM 5.0EC002637ETIM 6.0EC002637
UNSPSC 13.239121409

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CCV 2,5/16-GF-5,08-LR P26THR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.