INDUSTRIAL COMPONENT DATA

CCVA 2,5/ 3-G P26 THR R32 1087676 PHOENIX CONTACT Housing base printed circuit board, nominal current: 12 A,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CCVA 2,5/ 3-G P26 THR R32

PRODUCT IMAGE\nNOT AVAILABLE

Manufacturer	PHOENIX CONTACT
MPN / Reference	CCVA 2,5/ 3-G P26 THR R32
Catalog number	1087676
Category	Printed circuit board connector
Minimum order	140 Pcs
Document ID	EO-015A9F1A7D
Generated	2026-11-19

Product Overview

Housing base printed circuit board, nominal current: 12 A, number of poles: 3, pitch: 5 mm, color: black, surface of contact: Tin, assembly: Soldering THR
Printed circuit board base case, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Male, number of rows: 1, number of poles: 3, family of articles: CCVA 2.5/.. -G, pitch: 5 mm, mounting: Weld THR, pin arrangement: Linear pin arrangement, pin length [P]: 2.6 mm, number of welding pins per potential: 1, plug-in system: COMBICON MSTB 2.5, Plug-in face orientation: Standard, lock: without, fixing type: without, packaging type: 32 mm wide strap

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CCVA 2,5/ 3-G P26 THR R32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.