INDUSTRIAL COMPONENT DATA

CHARX AC-DIS/150KW 1342893 PHOENIX CONTACT CHARX power distribute, AC distribution unit for the assembly of ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: CHARX AC-DIS/150KW



Manufacturer	PHOENIX CONTACT
MPN / Reference	CHARX AC-DIS/150KW
Catalog number	1342893
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-C19821558E
Generated	2026-11-19

Product Overview

CHARX power distribute, AC distribution unit for the assembly of DC charging stations, 19 rack mounting, output: 400 V AC... 480 V AC / 54 A, 6 A
CHARX power distribute, 19" rack mount

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT

Additional Product Information

Technical dataInput DataAC Operation
Input voltage range 3x 400 V AC ... 480 V AC -15 % ... +10 %
Frequency 50 Hz ... 60 Hz ±10 %
Input current 3x 232 A
Configuring the Power Network Star Mesh (TN-S, TT)
Output DataRated power 150 kW
Relay signal
Identifying Connections Temperature Sensor (OTD)
Function Operational Status Forwarding
Changeover contact (potential-free) Contact open at rest
Switchable voltage 30 V DC
Current Rating 1 A
Relay signal

Identifying Connections Surge Protection (SPD)
Function Operational Status Forwarding
Changeover contact (potential-free) Contact open at rest
Switchable voltage 30 V DC
Current Rating 1 A
External periphery power supply
Number of outputs 5
Output voltage range 3x 400 V AC ... 480 V AC (L1... L3)
External periphery power supply
Number of outputs 1
Output voltage range 3x 400 V AC ... 480 V AC (L1... L3, N)
Connection dataInput power
Denomination Input power
Conductor connection
Connection Type T-LOX articulated lever connection
flexible with ferrule without plastic collar 0.25 mm² ... 2.5 mm²
flexible ferrule with plastic collar 0.25 mm² ... 1.5 mm²
Length of the section to be stripped 25 mm
Output power
Denomination Output power
Conductor connection
Connection Type Push-in spring connection
rigid 1.5 mm² ... 16 mm²
flexible 1.5 mm² ... 16 mm²
Length of the section to be stripped 18 mm
Signals
Denomination Signals
Conductor connection
Connection Type Push-in spring connection
rigid 0.2 mm² ... 4 mm²
flexible with ferrule without pla...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / CHARX AC-DIS/150KW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.