INDUSTRIAL COMPONENT DATA

P-CO 3036796 PHOENIX CONTACT Component connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: P-CO



Manufacturer	PHOENIX CONTACT
MPN / Reference	P-CO
Catalog number	3036796
Category	Component plug terminal block
Minimum order	10 Pcs
Document ID	EO-418CA71DC7
Generated	2026-11-18

Product Overview

Component connector
Component connector, for mounting self-selecting components, rated voltage: 250 V, rated current: 6 A, connection type: Plug-in connection, pitch: 5.2 mm, length: 24.2 mm, width: 5.1 mm, height: 24.2 mm, number of poles: 1, color: gray, mounting class: Plug-in (Slot)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data
Orderkey 3036796
Packing unit 10 pc
Minimum order quantity 10 pc
Catalog page Page 410 (C-1-2017)
GTIN 4017918929145
Weight per Piece (excluding packing) 3.510 g
Custom tariff number 85366990
Country of origin PL (Poland)
General
Note Notes on operation Components with a wire diameter from 0.5 mm up to 0.8 mm can be used
Number of positions 1
Potentials 1

Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Dimensions
Width 5.1 mm
Length 24.2 mm
Height 33.3 mm
Pitch 5.2 mm
General
Maximum load current 6 A
Nominal current IN 6 A
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Static insulating material application in cold -60 °C
Behavior in fire for rail vehicles (DIN 5510-2) Test passed
Flame test method (DIN EN 60695-11-10) V0
Oxygen index (DIN EN ISO 4589-2) >32 %
NF F16-101, NF F10-102 Class I 2
NF F16-101, NF F10-102 Class F 2
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Connection data
Connectio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / P-CO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.