
INDUSTRIAL COMPONENT DATA

FMC 1,5/ 4-STF-3,81 BD:PE-24V 1701307 PHOENIX CONTACT Cable connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: FMC 1,5/ 4-STF-3,81 BD:PE-24V



Manufacturer	PHOENIX CONTACT
MPN / Reference	FMC 1,5/ 4-STF-3,81 BD:PE-24V
Catalog number	1701307
Category	Cable connector
Minimum order	50 Pcs
Document ID	EO-ECEC799B08
Generated	2026-11-18

Product Overview

Cable connector
Connector for printed circuit board, nominal section: 1.5 mm², color: green, nominal current: 8 A, nominal voltage (III/2): 160 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: FMC 1.5/.. -STF, pitch: 3.81 mm, connection type: Push-in spring connection, driver/printed circuit board connection direction: 0°, plug-in system: COMBICON MC 1.5, lock: Screw lock, fixing type: Air clamp (screw), packaging type: boxed

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data
Orderkey 1701307
Packing unit 50 pc
Minimum order quantity 50 pc
Note Made to Order (non-returnable)
Catalog page Page 140 (C-8-2013)
GTIN 4046356525268
Weight per Piece (excluding packing) 2.990 g
Custom tariff number 85366990
Country of origin DE (Germany)

Dimensions
Length [l] 22.9 mm
Width [w] 25.33 mm
Height [h] 7.8 mm
Pitch 3.81 mm
Dimension a 11.43 mm
General
Range of articles FMC 1,5/..-STF
Number of positions 4
Connection method Push-in spring connection
Rated voltage (III/3) 160 V
Connection in acc. with standard EN-VDE
Nominal current IN 8 A
Nominal cross section 1.5 mm²
Connection data
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 1.5 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 1.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 1.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 0.75 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 16
Minimum AWG according to UL/CUL 24
Maximum AWG according to UL/CUL 16
Specifications for ferrules
Recommended crimping pliers 1212034 CRIMPFOX 6
Ferrules without insulating collar, according to DIN 46228-1 Cross section: 0.25 mm²; Length: 5 mm ... 7 mm
Cross section: 0.34 mm²; Length: 7 m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FMC 1,5/ 4-STF-3,81 BD:PE-24V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.