INDUSTRIAL COMPONENT DATA

UC-WMC 3,1 (15X 4) CUS 0824692 PHOENIX CONTACT Conductor marker

Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-WMC 3,1 (15X 4) CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	UC-WMC 3,1 (15X 4) CUS
Catalog number	0824692
Category	Cable coding system
Minimum order	1 Pcs
Document ID	EO-522676D0BE
Generated	2026-11-18

Product Overview

Conductor marker
Conductor marker, available: by mats, white, labeled according to customer's instructions, mounting class: hook, cable diameter range: 1.9 ... 3.1 mm, usable surface: 15 x 4 mm, Number of individual indices: 20
Conductor marker, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: clip on, cable diameter range: 1.9 ... 3.1 mm, Number of individual labels: 20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on

Additional Product Information

Technical dataProduct propertiesProduct type Labeled conductor marker
Type Card form
Data management status
Article revision 02
Marking
Number of individual labels 20
Number of individual labels per row 4
MountingMounting type clip on
Material specificationsRoHS compliant yes
Color white (RAL 9010)
Material PA

Flammability rating according to UL 94 V2
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 120 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 2
Components free from silicone and halogen
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
UV resistance
Specification ISO 4892-2:2013-03 (following)
Result Test passed
Test duration 96 h
Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport) 23 °C
Recommended humidity (storage/transport) 50 %
DimensionsWidth 4 mm
Length 15 mm
External dimensions
Outside diameter 1.9 mm ... 3.1 mm
Standards and regulationsWipe resistance DIN EN 61010-1 (VDE 0411-1)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC-WMC 3,1 (15X 4) CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.