INDUSTRIAL COMPONENT DATA

# UC-WMC 3,1 (30X4) OG CUS 0824722 PHOENIX CONTACT Conductor marker

**Brand: PHOENIX CONTACT | Manufacturer Part Number: UC-WMC 3,1 (30X4) OG CUS**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | UC-WMC 3,1 (30X4) OG CUS |
| Catalog number | 0824722 |
| Category | Cable coding system |
| Minimum order | 1 Pcs |
| Document ID | EO-58610BCE0D |
| Generated | 2026-11-18 |

## Product Overview

Conductor marker
Conductor marker, available: by mats, orange, labeled according to customer indications, mounting class: hook, cable diameter range: 1.9 ... 3.1 mm, usable surface: 30 x 4 mm, Number of individual indices: 12

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > CABINET add-on |

## Additional Product Information

Key Commercial Data
Orderkey 0824722
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 165 (C-5-2013)
GTIN 4046356360555
Weight per Piece (excluding packing) 8.700 g
Custom tariff number 49119900
Country of origin DE (Germany)
Dimensions
Length (b) 30 mm
Width (a) 4 mm
Cable diameter 1.9 mm ... 3.1 mm

Ambient conditions
Ambient temperature (operation) -40 °C ... 120 °C
Recommended storage conditions 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
General
Color orange
Type Card form
Components free from silicone and halogen
Flammability rating according to UL 94 V2
Material PA
RoHS compliant Yes
Wipe resistance DIN EN 61010-1 (VDE 0411-1)
Number of individual labels 12
Number of individual labels per row 4
Printability UV LED technology
Device 5147999 BLUEMARK CLED
Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02
Result Test passed
Test specification weathering-resistance Following ISO 4892-2:2013-03
Test duration 96 h
Wipe resistance test result Test passed
Salt spray test specification DIN EN 60068-2-11:2000-02
Salt spray testing result Test passed
Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07
Result Test passed
Marking mounting type clip on
Result Test passed
Oxygen index (DIN EN ISO 4589-2) 28,2%
Class I 3
Class F 2
R22 HL 1 - HL 2
R23 HL 1 - HL 2
R24 HL 1 - HL 2
Standards and Regulations
Wipe resistance DIN EN 6101...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UC-WMC 3,1 (30X4) OG CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.



Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.