INDUSTRIAL COMPONENT DATA

UCT-WMCO 3,5 (18X4) 0830783 PHOENIX CONTACT Conductor marking

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCT-WMCO 3,5 (18X4)



Manufacturer	PHOENIX CONTACT
MPN / Reference	UCT-WMCO 3,5 (18X4)
Catalog number	0830783
Category	Cable coding system
Minimum order	7 Pcs
Document ID	EO-E13DA45C7A
Generated	2026-11-18

Product Overview

Conductor marking
Conductor marking, Mat, white, unlabeled, labelable with: TOPMARKNEO, TOPMARK LASER, BLUEMARKIDCOLOR, BLUEMARKID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting class: hook, cable diameter range: 2.9 ... 3.5 mm, usable area: 18 x 4 mm, Number of individual indexes: 32
Wire marking, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: clip on, cable diameter range: 2.9 ... 3.5 mm, Number of individual labels: 32, text field height: 4 mm, text field width: 18 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > MS Material

Additional Product Information

Technical dataProduct propertiesProduct type Conductor marking
Type Card form
Data management status
Article revision 02
Marking
Number of individual labels 32
Number of individual labels per row 8
DimensionsWidth 4 mm

Text field width 18.00 mm
Text field height 4.00 mm
Length 18 mm
External dimensions
Outside diameter 2.9 mm ... 3.5 mm
Material specificationsColor white (RAL 9010)
Material PC
Flammability rating according to UL 94 V0
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Components free from silicone, halogen, and cadmium
Cable/lineExternal cable diameter 2.9 mm ... 3.5 mm
Environmental and real-life conditionsTest for substances that would hinder coating with paint or varnish
Result Test passed
Test for substances that would hinder coating with paint or varnish
Result Test passed
Scratch test for the determining scratch resistance
Specification EN ISO 1518-1:2023 (following)
Requirements >= 5 N
Result Test passed
Tesafilm test
Specification DIN EN ISO 2409:2020-12 (following)
Result Test passed
UV resistance
Specification DIN EN ISO 4892-2:2021-11 (following)
Result Test passed
Test duration 96 h
Temperature resistance
Specification ANSI/UL 969-2018:03 (following)
Test duration 240 h
Rating 100 °C (121 °C) Test passed
Wipe resistance of inscriptions
Specification DIN EN 61010-1 (VDE 0411-01):2020-03
DIN EN 62208 (...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCT-WMCO 3,5 (18X4) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.