INDUSTRIAL COMPONENT DATA

VS-ASI-FC-TPE-UL-YE 1000M 1434662 PHOENIX CONTACT Flat-ribbon conductor

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-ASI-FC-TPE-UL-YE 1000M



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-ASI-FC-TPE-UL-YE 1000M
Catalog number	1434662
Category	Data cable
Minimum order	1 Pcs
Document ID	EO-BD8EC2D07B
Generated	2026-11-19

Product Overview

Flat-ribbon conductor
AS-Interface TPE flat cable with UL in yellow, 2 x 1.5 mm², 1000 m on disposable drum

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data
Orderkey 1434662
Packing unit 1 pc
Note Made to Order (non-returnable)
Catalog page Page 438 (C-2-2017)
GTIN 4046356349307
Weight per Piece (excluding packing) 222.220 g
Custom tariff number 85444995
Country of origin DE (Germany)
Mechanical characteristics
Number of positions 2
Shielded no
Type of cable Flat-ribbon conductor
Cable structure 2x 1.5 mm²

Duty cycle testing suitable for drag chain
Length of cable 1000 m
Ambient conditions
Ambient temperature (operation) -40 °C ... 105 °C (fixed routing)
-30 °C ... 105 °C (Flexibly installed)
Ambient temperature (assembly) -30 °C ... 105 °C
Ambient temperature (storage/transport) -40 °C ... 105 °C
Material data
Outer sheath, material TPE
External sheath, color yellow
Height 4 mm
Electrical characteristics
Rated voltage (III/3) 300 V
Rated surge voltage 2 kV
Standards and Regulations
Duty cycle testing suitable for drag chain
Line characteristics
Type of cable Flat-ribbon conductor
Cable structure 2x 1.5 mm²
Conductor cross section 1.5 mm²
AWG signal line 16
Conductor structure signal line 84x 0.15 mm
Core diameter including insulation 2.5 mm
Thickness, insulation approx. 0.5 mm
Wire colors brown, blue
External sheath, color lemon yellow RAL 1012
Insulation resistance >= 1 M?*km
Conductor resistance <= 13.7 ?/km
Nominal voltage, cable 300 V
Test voltage, cable 2000 V
Outer sheath, material TPE
Material conductor insulation TPE
Conductor material Bare Cu litz wires
Cable weight 64 kg/km
Smallest bending radius, f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-ASI-FC-TPE-UL-YE 1000M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.