
INDUSTRIAL COMPONENT DATA

# MINI MCR-2-RTD-UI 2902049 PHOENIX CONTACT Resistance thermometer measuring transducer

**Brand: PHOENIX CONTACT | Manufacturer Part Number: MINI MCR-2-RTD-UI**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | MINI MCR-2-RTD-UI |
| Catalog number | 2902049 |
| Category | Temperature transformer |
| Minimum order | 1 Pcs |
| Document ID | EO-29930A2743 |
| Generated | 2026-11-18 |

## Product Overview

Resistance thermometer measuring transducer
Configurable temperature converter with plug-in connection technology for the connection of 2, 3, 4 conductor resistance heaters and transmitters. Configurable via DIP switch or software. Screw connection technology, standard configuration

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > INTERFACE Components (IF) |

## Additional Product Information

Key Commercial Data
Orderkey 2902049
Packing unit 1 pc
Catalog page Page 80 (C-5-2017)
GTIN 4046356649759
Weight per Piece (excluding packing) 110.000 g
Custom tariff number 85437090
Country of origin DE (Germany)
Note
Utilization restriction EMC: class A product, see manufacturer's declaration in the download area
Dimensions
Width 6.2 mm
Height 110.5 mm

Depth 120.5 mm
Ambient conditions
Ambient temperature (operation) -40 °C ... 70 °C
Ambient temperature (storage/transport) -40 °C ... 85 °C
Input data
Configurable/programmable Yes
Sensor types (RTD) that can be used Pt, Ni, Cu sensors
Linear resistance measuring range 0 ? ... 4000 ? (Minimum measuring span: 10% of the selected measuring range)
Sensor input current approx. 200 µA
Temperature measuring range -200 °C ... 850 °C (Range depends on sensor type, range can be set freely via software or in increments from -150°C to 850°C via DIP switches)
Connection technology 2, 3, 4-wire
Output data
Number of outputs 1
Configurable/programmable Yes
Voltage output signal 0 V ... 5 V (via DIP switch)
1 V ... 5 V (via DIP switch)
0 V ... 10 V (via DIP switch)
10 V ... 0 V (via DIP switch)
0 V ... 10.5 V (can be set via software)
Current output signal 0 mA ... 20 mA (via DIP switch)
4 mA ... 20 mA (via DIP switch)
20 mA ... 0 mA (via DIP switch)
20 mA ... 4 mA (via DIP switch)
0 mA ... 21 mA (can be set via software)
Max. output voltage approx. 12.3 V
Max. output current 24.6 mA
Short-circuit current < 31.5 mA
Load/output load voltage...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MINI MCR-2-RTD-UI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.