INDUSTRIAL COMPONENT DATA

PSD-S CE-SM SPRING 2700091 PHOENIX CONTACT Connection element

Brand: PHOENIX CONTACT | Manufacturer Part Number: PSD-S CE-SM SPRING



Manufacturer	PHOENIX CONTACT
MPN / Reference	PSD-S CE-SM SPRING
Catalog number	2700091
Category	Connection module for signal tower
Minimum order	1 Pcs
Document ID	EO-1EA0D1F4F6
Generated	2026-11-18

Product Overview

Connection element
Connecting element with spring-loaded terminal blocks for floor mounting
Connection element with spring-cage terminal blocks for base mounting

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Control Systems (CST)

Additional Product Information

Technical dataNotesNote on application
Note on application Only for industrial use
Product propertiesProduct type Assembly element
Scope of delivery End cover and seal
End cover and seal
Number of mountable signal elements max. 5
Data management status
Article revision 00
Electrical propertiesGeneral
Nominal input voltage range 12 V AC/DC ... 240 V AC/DC
Connection datawithout ferrule
Connection method Spring-cage connection
Conductor cross section, flexible 0.5 mm² ... 1.5 mm²

Conductor cross section, flexible [AWG] ... 15
Stripping length 7 mm
With ferrule
Connection method Spring-cage connection
Conductor cross section, flexible 0.25 mm² ... 1.5 mm²
Conductor cross section, flexible [AWG] ... 15
Stripping length 7 mm
solid
Connection method Spring-cage connection
Conductor cross section, rigid 0.5 mm² ... 1.5 mm²
Stripping length 7 mm
DimensionsDimensional drawing
Height 27 mm
Diameter 69 mm
Material specificationsColor black
Material PA-GF
Environmental and real-life conditionsAmbient conditions
Degree of protection IP65, when installed
Ambient temperature (operation) -30 °C ... 50 °C
EMC dataElectromagnetic compatibility Conformance with EMC directive 2004/108/EC and for low-voltage directive 2006/95/EC
MountingMounting type Base mounting
Assembly note Rubber seal pre-installed for each element
Mounting position any

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PSD-S CE-SM SPRING with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.