INDUSTRIAL COMPONENT DATA

# K-5E-M40 M9/5,0-C06/M40 F8 1620380 PHOENIX CONTACT Connector in molded plastic on both sides

**Brand: PHOENIX CONTACT | Manufacturer Part Number: K-5E-M40 M9/5,0-C06/M40 F8**



| | |
|---|---|
| Manufacturer | PHOENIX CONTACT |
| MPN / Reference | K-5E-M40 M9/5,0-C06/M40 F8 |
| Catalog number | 1620380 |
| Category | Flexible cable |
| Minimum order | 2 Pcs |
| Document ID | EO-9B8B856B1D |
| Generated | 2026-11-19 |

## Product Overview

Connector in molded plastic on both sides
Plug-in connector coated with plastic on both sides, series: KSM, M40-Female, straight coated by plastic extrusion, number of poles: 2+3+PE, Lock type: Screw lock, to M40-Male, straight coated by plastic extrusion, number of poles: 2+3+PE, cable length: 5 m, shielded: yes, outer wrap color: orange RAL 2003

STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

| | |
|---|---|
| Catalog path | PHOENIX CONTACT > Field Device Connectors (FDC) |

## Additional Product Information

Key Commercial Data
Orderkey 1620380
Packing unit 1 pc
Minimum order quantity 2 pc
Note Made to Order (non-returnable)
Catalog page Page 231 (C-2-2017)
GTIN 4046356833707
Weight per Piece (excluding packing) 2,220.000 g
Custom tariff number 85444290
Country of origin DE (Germany)
Conductor length 5 m
Nominal current 61 A

Connector specifications
Type straight plastic-sheathed
Thread type M40
Locking type Screw locking
Degree of protection IP67, when in locked state
Number of positions 2+3+PE
Direction of rotation Standard
Type of contact Socket
Insertion/withdrawal cycles 50
Contact resistance < 0.3 m?
Max. current 70 A
Voltage 630 V
Overvoltage category III
Degree of pollution 3
Rated surge voltage 6 kV
Ambient temperature (operation) -40 °C ... 105 °C
Cable specifications
Type of cable PSLC11Y-J
Shielded yes
Cable structure 4 x 10 mm² + 2 x 1.5 mm²
Cable structure (AWG) 8 AWG/4c + 16 AWG/1pr
External cable diameter 18.1 mm
Outer sheath, material TPU
Material wire insulation TPM
External sheath, color orange RAL 2003
Nominal voltage, cable 1000 V
Test voltage 4 kV (2 kV signal)
Rated current 61 A
Smallest bending radius, movable installation 218 mm
Ambient temperature for fixed installation -50 °C ... 80 °C
Ambient temperature for flexible installation -20 °C ... 70 °C
Connector specifications (second page)
Type straight plastic-sheathed
Housing material Zinc die-cast
Thread type M40
Degree of protection IP67, when in locked state
Number of positions 2+3+PE
Direction of rot...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / K-5E-M40 M9/5,0-C06/M40 F8 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.