INDUSTRIAL COMPONENT DATA

SACC-CI-M12FSD-4CON-L90 SCO 1432457 PHOENIX CONTACT Flush-type connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: SACC-CI-M12FSD-4CON-L90 SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SACC-CI-M12FSD-4CON-L90 SCO
Catalog number	1432457
Category	Contact insert for circular connectors
Minimum order	20 Pcs
Document ID	EO-49A3301DD9
Generated	2026-11-18

Product Overview

Flush-type connector
Plug-in Mounting Connector, Ethernet / PROFINET CAT5 (100 MBit/s), 4-Pole, Female Connection, Straight, M12, Coding: D, Printed Circuit Board Mounting, Solder Pins, Alternative product according to RoHS II without exception 6c (Pb< 0.1%)
Item code: 1237421

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data
Orderkey 1432457
Packing unit 20 pc
Minimum order quantity 20 pc
Catalog page Page 252 (C-2-2013)
GTIN 4046356410748
Weight per Piece (excluding packing) 4.030 g
Custom tariff number 85366990
Country of origin DE (Germany)
Ambient conditions
Ambient temperature (operation) -25 °C ... 105 °C (Plug / socket)
-40 °C ... 105 °C (without mechanical actuation)

Degree of protection IP67
General
Note The electrical and mechanical data specified assume that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of contamination, the connector must be sealed using a protective cap > IP54. Influences arising from litz wires, cables or PCB assembly must also be taken into consideration.
Rated current at 40°C 4 A
Rated voltage 250 V
Rated surge voltage 2.5 kV
Number of positions 4
Insulation resistance >= 100 M?
Coding D - data
Standards/regulations M12 connector IEC 61076-2-101
Status display No
Overvoltage category II
Degree of pollution 3
Connection method Solder pins
Insertion/withdrawal cycles > 100
Mounting type PCB mounting
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA 6.6
Sealing material FKM / EPDM
Cable
Standards/specifications M12 connector IEC 61076-2-101
Ambient temperature (operation) -40 °C ... 105 °C (cable, fixed installation)
-25 °C ... 105 °C (cable, flexible installation)
Standards and Regulations
Standard designation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SACC-CI-M12FSD-4CON-L90 SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.